

# 10G XGSPON ONU BOSA Receptacle SC APC

|                     |  |
|---------------------|--|
| <b>Product</b>      | <b>10G XGSPON ONU BOSA Receptacle SC APC</b> |
| <b>P/N</b>          | <b>13530222</b>                              |
| <b>File No.</b>     | <b>#605006</b>                               |
| <b>Version</b>      | <b>1.0</b>                                   |
| <b>Issuing Date</b> | <b>2024-03-18</b>                            |



| Specification Revision Record |         |      |                      |         |         |
|-------------------------------|---------|------|----------------------|---------|---------|
| Date                          | Version | Page | Revision Description | Prepare | Approve |
| 20240318                      | 1.0     |      |                      | CTL     |         |
|                               |         |      |                      |         |         |

All right reserved by Guilin GLsun Science and Tech Group Co., LTD. Without written permission, any unit or individual can't reproduce, copy or use it for any commercial purpose.

# 10G XGSPON ONU BOSA Receptacle SC APC

## BA-53 Series T10G/R10G

### ■ Description

This BOSA is a high performance optical sub-assembly in single fiber by using 1270nm transmitter and 1577nm receiver. The transmitter section uses a multiple quantum well 1270nm DFB laser supporting burst-mode operation. The receiver section uses an integrated 1577nm APD and preamplifier mounted in a TO-can.

### ■ Features

- Single fiber pigtail type bi-directional transmission design for 10G XGSPON ONU.
- Symmetric 10GbpsTx and 10GbpsRx data rate.
- Integrated micro-optics WDM filters for dualwavelength Tx/Rxoperation at 1270/1577nm.
- 1270nm InGaAsP/InPMQW DFB laser diode transmission with InGaAs monitor photodiode.
- 1577nm digital APD-TIA continuous mode receiver.
- Optical reflection free with built-in 1270nm free space isolator.
- High optical isolation from external 1577nm source, and low optical cross-talk from internal 1270nm source.
- -40°C to +85°C temperature with excellent temperature dependent power tracking error.

### ■ Application

- 10G XGSPON symmetric SFP+ transceiver, ONU
- 10 G Ethernet Access Networks symmetric SFP+, ONU

### ■ Standard

- ITU-T 987.2 10GXGPON-2 communication protocol
- Compliant with TelcordiaGR-468 reliability test criterion
- Compliant with TelcordiaGR-326 connector qualification standard
- Compliant with RoHS6 standard

### ■ Absolute Maximum Ratings

| Item                    | Unit | Min | Max | Note |
|-------------------------|------|-----|-----|------|
| Forward Current for LD  | mA   | --  | 120 |      |
| Reverse Voltage for LD  | V    | --  | 2   |      |
| Forward Current for MPD | mA   | --  | 2   |      |
| Reverse Voltage for MPD | V    | --  | 20  |      |

|                           |    |      |     |      |
|---------------------------|----|------|-----|------|
| APD Reverse Current       | mA | --   | 2   |      |
| APD Reverse Voltage       | V  | --   | Vbr |      |
| TIA Supply Voltage        | V  | -0.4 | 4   |      |
| Operating Temp            | °C | -40  | 85  |      |
| Storage Temperature       | °C | -40  | 85  |      |
| Storage Relative Humidity | %  | --   | 85  |      |
| Soldering Temperature     | °C | --   | 260 | (*1) |
| ESD threshold             | V  | 500  | --  |      |

(\*1): For soldering by iron and 10 seconds on leads

### Transmitter Electro-Optical Characteristics (TC=25°C, CW)

| Item                        | Symbol          | Test Condition                                      | Min. | Typ.  | Max. | Unit |
|-----------------------------|-----------------|---|------|-------|------|------|
| Transmitter Bit Rate        | BR              | --  | --   | 9.953 | --   | Gbps |
| Threshold Current           | I <sub>th</sub> | 25°C  | --   | 7.5   | 15   | mA   |
|                             |                 | -40~85°C  | --   | --    | 40   | mA   |
| Optical Output Power (*2)   | P <sub>f</sub>  | CW, I <sub>f</sub> =I <sub>th</sub> +20mA           | 2.5  | --    | 6.0  | mW   |
|                             |                 | CW, I <sub>f</sub> =I <sub>th</sub> +20mA, -40~85°C | 1.0  | --    | --   | mW   |
| Forward Voltage             | V <sub>f</sub>  | CW, I <sub>f</sub> =I <sub>th</sub> +20mA           | --   | --    | 1.8  | V    |
| Peak Wavelength             | λ <sub>c</sub>  | CW, I <sub>f</sub> =I <sub>th</sub> +20mA           | 1260 | 1270  | 1280 | nm   |
| Spectrum Width (-20dB)      | Δλ              | CW, I <sub>f</sub> =I <sub>th</sub> +20mA           | --   | --    | 1.0  | nm   |
| Side Mode Suppression Ratio | SMSR            | CW, I <sub>f</sub> =I <sub>th</sub> +20mA           | 30   | --    | --   | dB   |
| Monitor Current             | I <sub>m</sub>  | CW, I <sub>f</sub> =I <sub>th</sub> +20mA           | 100  | --    | 1200 | μA   |
| Monitor Dark Current        | I <sub>d</sub>  | V <sub>rp</sub> =5V                                 | --   | --    | 100  | nA   |
| Monitor Capacitance         | C               | CW, V <sub>rp</sub> =5V, f=1MHz                     | --   | 10    | 20   | pF   |
| Tracking Error(*3)          | TE              | CW, T <sub>c</sub> =-40~85°C                        | -1.5 | --    | 1.5  | dB   |

(\*2): Launched into 9/125μm SMF

(\*3): P<sub>f</sub> = 10xlog(P<sub>f</sub>(T<sub>c</sub>) / P<sub>f</sub>(25°C)), I<sub>m</sub> hold(@P<sub>f</sub>=2.5mW, 25°C)

### Receiver Optical-Electro Characteristics (TC=25°C, V<sub>cc</sub>=3.3V)

| Item                 | Symbol          | Test Condition         | Min. | Typ.  | Max.  | Unit |
|----------------------|-----------------|------------------------|------|-------|-------|------|
| Receiver Bit Rate    | BR              | --                     | --   | 9.953 | --    | Gbps |
| Supply Voltage       | V <sub>cc</sub> | No loads               | 3.0  | 3.3   | 3.6   | V    |
| Supply Current       | I <sub>cc</sub> | No loads               | 20   | 33    | 45    | mA   |
| Operating Wavelength | λ               | --                     | 1575 | 1577  | 1580  | nm   |
| Sensitivity          | Sen             | 9.953Gbps, 1577nm, NRZ | --   | --    | -30.0 | dBm  |

